

Engine

- ♦ Cummins
- ♦ 5,9 L
- ♦ 170 HP
- ♦ Turbo and Aftercooled

Cabin

- ♦ 2 doors
- ♦ Air Conditioning
- ♦ 2 rear-view mirrors
- ♦ Operational indicators

Transmission

- ♦ Hydrostatic
- ♦ Maximum travel speed 16 Km/h

Capacities

- ♦ Fuel tank: 210L
- ♦ Hydraulic oil tank: 130 L

Tires

- ♦ Front (10.0 x16 - 8 lonas)
- ♦ Rear (14.9 x 28 x 10 lonas)

Crop Dividers

- ♦ Distance between point: 1.100mm
- ♦ Spiral angle: 30 °
- ♦ Hydraulic adjustable height
- ♦ lower section increased

Base Cutter

- ♦ Hydraulic and reversible drive
- ♦ 2 identical and reversible disks
- ♦ 8 removable blades
- ♦ Distance between the center of the disc: 495 mm

**Cutter tips**

- ♦ Hydraulic adjustable height
- ♦ Height change: 1050 to 3000 mm

Knockdown roller

- ♦ Adjustable height
- ♦ Angle: 51 °

Feed roller train

- ♦ Number of Rollers: 11
- ♦ Number of rolls in the train of rolls: 8
- ♦ Hydraulic and reversible drive
- ♦ Top floating rollers

Choppers

- ♦ Number of blades per roll: 2
- ♦ Throwers
- ♦ Adjustable deflectors

Extractors

- ♦ 3 fan blades
- ♦ Directional Hood
- ♦ Guide wear

Elevator

- ♦ Hydraulic and reversible drive
- ♦ Spin angle 170 °

Weight

- ♦ 6.700 Kg

Wheel Track

- ♦ 1.360 mm

Parts

- ♦ Expressive amount of interchangeable parts with the big Case IH machines