

M-SERIES 3PT



- The time proven range



"The heart of the sprayer"



HARDI diaphragm pump: The diaphragms separate the liquid from the vital parts of the pump such as bearings, connecting rods and crankshaft. Ensuring reliable and durable operation.

"Powder painted steel"



Chassis: N-Series 3pt. chassis is zinc-phosphate treated before being coated with polyester powder. This ensures outstanding weather and chemical resistance on all chassis parts.



"Polyethylene tanks"



The high-impact polyethylene tank has a deep sump that ensures complete emptying of the tank.

"Fluid operating units"



HARDI manual or Electric control: A long list of standard features which ensure accurate and reliable application of all plant protection chemicals.

"Boom range"

Range of Booms: SB boom from 20' to 33' - MB booms 40' widths and Pasture booms 30' to 50'



"Technical Specification"

Tank Size US/gal	Boom width	Boom model	Pump model	Pump Capacity gal/min	Size L X W X H (inches)	Weight lbs
105	20'	SB	603/1203 1303	10/20/30	55x75x67	331
105	26'	SB	603/1203 1303	10/20/30	55x75x 83	334
155	20'	SB	603/1203 1303	10/20/30	55x75x 67	362
155	26'	SB	603/1203 1303	10/20/30	55x75x83	375
155	33'	SB	1203/1303	20/30	55x75x83	415
155	40'	MB	1203/1303	20/30	59x89x87	520
210	20'	SB	603/1203 1303	10/20/30	55x101x96	400
210	26'	SB	603/1203 1303	10/20/30	55x101x102	419
210	33'	SB	1203/1303	20/30	55x101x102	459
210	40'	MB	1203/1303	20/30	59x89x87	576

